



TYPE 27

DEPRESSED CENTER GRINDING WHEELS FOR PORTABLE ANGLE GRINDERS



GRINDING

The wide range of GLOBE grinding wheels offers different levels of hardness and different removal rates in order to provide the operator with the possibility to choose the most suitable type for the work to be carried out. GLOBE wheels are designed respecting strict limits of unbalancing in order to guarantee the minimum level of vibrations during use. The quality characteristics of GLOBE wheels enhance the economic efficiency of use in every context, as demonstrated by control and comparative tests conducted in the company laboratories. All the wheels designed for stainless steel have contents of Iron, Sulphur, and Chlorine compounds lower than 0.1%, as indicated on the label (certification available). GLOBE offers a large number of different specifications for the materials to be worked. The choice of the right type is an element of fundamental importance to obtain maximum performance..

MATERIAL	DIMENSIONS (diam - thick. - bore) mm	HARDNESS	VEL USO	ARTICLE CODE	
----------	---	----------	------------	-----------------	--

 **STAINLESS
STEEL AND
STEEL**

A 24 30 36 R: good removal rate and long durability. Suitable for grinding of jagged fins, sharp edges and welding of ferrous metals.

DISC DURABILITY
REMOVAL CAPACITY
REMOVAL ACCURACY



NEW	115x6,0x 22,23	A 24 30 36 R	80 m/s	G0122 DYN	25pz
NEW	125x6,0x22,23	A 24 30 36 R	80 m/s	G0123 DYN	25pz
NEW	180x6,5x22,23	A 24 30 36 R	80 m/s	G0211 DYN	25pz
NEW	230x6,5x22,23	A 24 30 36 R	80 m/s	G0213 DYN	25pz