

SAFECUT II e SAFECUT III

I **SAFECUT** discs combine in a single disc the cutting depth of the flat disc with the extreme precision of the depressed center (DC) disc. The depressed center shape gives rigidity to the disc, preventing it from bending or vibrating. Furthermore SAFECUT III offers in diameters 115 and 125 the innovating depressed center with **narrow dome** (Ø55 mm instead of 70 mm of conventional depressed center discs). This means: increased cutting depth and longer life. The safety guaranteed by GLOBE high standards is further increased by the metal dome that prevents damage of the depressed center and the consequent breakage of the disc that can occur when the surface of the dome rubs against the material you are cutting.



The SAFECUT special "ribs"



- Straight and net cut
- Does not bend or vibrate
- Extreme precision
- Very high cutting speed
- Long durability
- Safety in deep cuts
- Cutting depth
- Ease of handling and versatility

Flush cut possible thanks to the depressed center shape and the use of the "SPACER".

PATENTED

MATERIAL	DIMENSIONS (diam - thick - bore) mm	HARDNESS	USE SPEED	ARTICLE CODE	
----------	--	----------	-----------	--------------	--

PLUS LINE 


STEEL

A 60 S: suitable for cutting iron and steel. Fast and cold cut, long durability.

NEW
NEW

75x1,0x9,52	SafeCut II	A 60 S	80 m/s	G1537	100pz
115x1,3x22,23	SafeCut III	A 60 S	80 m/s	G1532	25pz
125x1,3x22,23	SafeCut III	A 60 S	80 m/s	G1533	25pz
150x1,6x22,23	SafeCut II	A 60 S	80 m/s	G1534	50pz
180x2,0x22,23	SafeCut II	A 60 S	80 m/s	G1535	50pz
230x2,0x22,23	SafeCut II	A 60 S	80 m/s	G1536	50pz

DISC DURABILITY
CUTTING SPEED
CLEAN CUT

