


CONCRETE MICRO-HAMMERING SYSTEM

Ref.
104



see our
video on
YouTube

WALLSTER

Hammer drill bit compatible SDS-plus

Features


- Semi positive carbide tip.
- Tip angle 130°.
- Short shaped length.
- Elongated pitch.
- Hammering reducer.
- Compatible SDS-plus shank.

Benefits

- The hammering reducer generates micro percussion and keeps the walls of the block safe from damage.
- Calibrated hole.
- Increased anchoring strength.
- The unshaped part of the flute provides rigidity and guides the bit along the line over the entire drilling depth.
- The flute shape makes removal easier while drilling through insulating material.

EFFICIENT IN ALL HOLLOW BLOCKS OF THE MARKET

Slap, breeze block, breeze block Easytherm®, Rubbe, hollow brick, brick for bonding, brick pole, brick rabbit Wienerberger®, plank, brick of arase...



Diager developed specially a bit to drill hollow blocks without degrading walls. This special dill bit for hollow blocks allows to realize qualitative holes which enhance reliability of the anchorings.



Ø	Ref.	Gencod	Qt.
L 100 x 160			
5	104D05L0160	3336600187214	1
6	104D06L0160	3336600187221	1
8	104D08L0160	3336600187238	1
10	104D10L0160	3336600187245	1
L 200 x 260			
6	104D06L0260	3336600182240	1
8	104D08L0260	3336600182103	1
10	104D10L0260	3336600182110	1
12	104D12L0260	3336600182127	1
14	104D14L0260	3336600182134	1
16	104D16L0260	3336600182141	1
L 400 x 460			
8	104D08L0460	3336600182158	1
10	104D10L0460	3336600182165	1

Plastic clip



PLV picking-counter
Delevry unmounted
Ref.C00084

**UP TO 3
TIMES
STRONGER
RESISTANCE**

COMPARATIVE TESTS: DRILLING AND ANCHORING IN A HOLLOW BLOCK

STANDARD drill bit

Drilling
The wall is damaged, only 7mm thickness remains.

Test of tearing for a chemical fixing
The fixation quickly gives in. Break in 250 kg.

250 Kg
↑
Pull out resistance



Hammer drill WALLSTER

Drilling
The wall is intact, and keeps its original thickness of 16mm.

Test of tearing for a chemical fixing
The fixation resists perfectly. It is the wall which gives in. Break in 700 kg.

700 Kg
↑
Pull out resistance

Tests made with a SDS + machine GBH 2 with hammering in hollow concrete block with a chemical anchor.

