

Ref.
U601S

Power socket

Surface protection socket

Features

- Attachment E6.3 DIN 3126.
- For hex head screw.

Benefits

- Specially adapted for screws used for fastening

front or sandwich panels and self-drilling screws.



Plastic box

Ø	TL	Ref.	Gencod	Qty
L50				
S07	50	U601S07	3336600181632	1
S08	50	U601S08	3336600181649	1
S10	50	U601S10	3336600181656	1
S1/4 (6,35mm)	50	U601S1/4	3336600181663	1
S5/16 (8mm)	50	U601S5/16	3336600181670	1
S3/8 (9,5mm)	50	U601S3/8	3336600181687	1

Ref.
U600

Pro magnetic socket

Magnetic socket length 50 mm for hexagonal metric screws.

Features

- Attachment E6.3 DIN 3126.
- For hex head screw.

Benefits

- Powerful magnet for holding screws.



Plastic box

Ø	TL	Ref.	Gencod	Qty
L50				
S05.5	50	U600S05.5	3336600187276	1
S06	50	U600S06	3336600173118	1
S07	50	U600S07	3336600172319	1
S08	50	U600S08	3336600172326	1
S09	50	U600S09	3336600190276	1
S10	50	U600S10	3336600172340	1
S12	50	U600S12	3336600172357	1
S13	50	U600S13	3336600172364	1
S1/4 (6;35mm)	50	U600S1/4	3336600172302	1
S5/16 (8mm)	50	U600S5/16	3336600192393	1
S3/8 (9,5mm)	50	U600S3/8	3336600192386	1

Ref.
U603

Pro magnetic socket

Magnetic socket length 65 mm for hexagonal metric screws.



Plastic box

Ø	TL	Ref.	Gencod	Qty
L65				
S05	65	U603S05	3336600187368	1
S05.5	65	U603S05.5	3336600187375	1
S06	65	U603S06	3336600187382	1
S07	65	U603S07	3336600187399	1
S08	65	U603S08	3336600187283	1
S10	65	U603S10	3336600187290	1
S12	65	U603S12	3336600190283	1
S13	65	U603S13	3336600187313	1

Features

- Attachment E6.3 DIN 3126.
- For hex head screw.