



## TECHNICAL DATA SHEET

# GREASE SPRAY WITH P.T.F.E.

### Characteristics

Base:	Silicone grease with PTFE
Temperature of application:	-30 °C / + 220 °C (approximately)
Appearance:	translucent grease
Propellant:	Denatured and odourless hydrocarbon
Solvents Free, CFC free, Not Toxic	

### Properties:

- It is a good penetrating grease
- High resistance to traction
- It prevents overheating and abrasion of the parts in contacts.
- Dielectric, isolating, protective.
- Water repellent (It can be used to lubricate underwater equipments)
- It contains PTFE that is a very good lubricant and penetrating agent.

### Description

ELEMATIC GREASE SPRAY is used for general lubrication purposes. It is used in mechanic industry especially to lubricate all mechanic parts where a good lubricant as silicone added with PTFE, is necessary. Lubricant for chains and gear wheels, ball bearings and any other mechanic movement.

### Instructions of use

Spray the product from 30 cm distance.

### Packaging

Spray Aerosol ml 400  
Box 25 Aerosol  
Product Code **8242001**



### Head office

ITW Construction Products Italy S.r.l.  
Via Lombardia 10, 30030  
Cazzago di Pianiga (VE)  
Zona Industriale  
e-mail: [info@itw-italy.com](mailto:info@itw-italy.com)  
[www.elematic.it](http://www.elematic.it)