



## TECHNICAL DATA SHEET

# SILICONE SPRAY

## SILICONE SPRAY, LUBRICANT, ANTIADHESIVE, SLIDING AGENT



### Characteristics

Base:	Silicone oil with middle viscosity
Propellant:	Denatured and odourless hydrocarbons (VOC Free)
Appearance:	Transparent and colourless liquid
Odour:	Odourless
Temperature of Resistance:	From -40 to + 250 °C
CFC free	
Chlorinate Free	
It isn't toxic	

### Properties:

- Good mould releasing agent for plastic and rubber.
- Good antistatic

### Description

SILICONE SPRAY is used in rubber and plastic industry, typography, serigraphy, leather, tailoring etc... It is a good mould releasing agent for plastic and rubber.

It lubricates the blades to cut paper and polyethylene. It is a good antistatic and sliding agent for worktops.

SILICONE SPRAY is also used in textile industry as lubricant for sewing machines, knitting machines, and antistatic for yarns.

It neither grease nor stains treated materials.

It leaves a very fine film that protect against oxidation.

### Instructions of use

Spray the products from 30 cm distance of the material to treat.

### Packaging

Spray Aerosol ml 500  
Box 25 Aerosol  
Product Code **8242003**

### Head office

ITW Construction Products Italy S.r.l.

Via Lombardia 10, 30030  
Cazzago di Pianiga (VE)  
Zona Industriale

e-mail: [info@itw-italy.com](mailto:info@itw-italy.com)

[www.elematic.it](http://www.elematic.it)