

## Nes26 Cat # 07263



	ØD Range	Pipes	L	B	H	ROD	Ør	ØR	Package Size			Weight	
									L	W	H	lb	gm
inch	1 <sup>1</sup> / <sub>4</sub> " - 2 <sup>5</sup> / <sub>8</sub> "	7 <sup>7</sup> / <sub>8</sub> " - 2 <sup>1</sup> / <sub>4</sub> "	6 <sup>7</sup> / <sub>16</sub> "	1 <sup>15</sup> / <sub>16</sub> "	3 <sup>5</sup> / <sub>8</sub> "	7 <sup>9</sup> / <sub>16</sub> "	1 <sup>5</sup> / <sub>8</sub> "	2 <sup>3</sup> / <sub>4</sub> "	8 <sup>3</sup> / <sub>16</sub> "	3 <sup>3</sup> / <sub>8</sub> "	1 <sup>5</sup> / <sub>8</sub> "	2.40	1100
mm	32-68		163	50	92	192	41	70	208	85	42		



\*Attachable sleeve (code 07259) included to use with diameters between 44-54 mm.

\*Attachable sleeve (code 07269) included to use with diameters between 54-68 mm.

### Replacement Blades:

- RK25 60° Cat # 07256C (fitted as standard)
- RK25 55° Cat # 07255C
- RK25 60° Cat # 07258F – best for threads finer than 14 TPI or 1.75mm
- RK25 55° Cat # 07252F – best for threads finer than 14 TPI or 1.75mm
- RK 26 60° Cat No. 07266C
- RK 26 60° Cat No. 07265C
- RK26 60° Cat # 07268F – best for threads finer than 14 TPI or 1.75mm
- RK26 55° Cat # 07262F – best for threads finer than 14 TPI or 1.75mm

N.B 55° blades are marked by Orange dot