782 XL | 783 XL

ART.	CODE I CÓDIGO
782 XL	8.48.46.22

TECHNICAL FEATURES

- Easy blade tensioning device
- Powerful 950 W single phase motor with digital electronic speed regulator "Constant speed" with amperometric limiting device (ART. 783XL)
- Two speeds, electronic switch (ART. 782XL).
- Anti-reset safety function
- Steady and sturdy pressed steel base.
- Arm-locking device for easy handling.

STANDARD EQUIPMENT

- Adjustable bar stop-rod for mass-produced cuts (L= 500mm).
- Blade cleaning felt spares kit
- Filter-circuit for electromagnetic interference damping according to rules in force.

CARACTERÍSTICAS TÉCNICAS

- Tensor de la hoja práctico de usar
- Potente motor 950 W con regulación electrónica de velocidad "Velocidad constante", con limitador amperimétrico (ART. 783XL)
- 2 velocidades de conmutación electrónica (ART. 782XL)
- Sistema de seguridad anti-arranque.
- Base de acero fundido estable y robusta.
- Dispositivo de bloqueo arco para facilitar el transporte.

EQUIPAMIENTO DE SERIE

- Varilla de sujeción de la barra regulable, para realizar cortes en serie (L= 500mm)
- Kit de recambio filtro de limpieza de la hoja
- Circuito-filtro para la eliminación de interferencias electromagnéticas conforme con las normativas vigentes

PATENTED

ART.	CODE I CÓDIGO
783 XL	8.48.46.23

WITHOUT LUBRICATION
SIN LUBRICACION

ELECTRONIC SPEED REGULATION

REGULACIÓN ELECTRÓNICA DE VELOCIDAD

CUTTING CAPACITY | CAPACIDAD DE CORTE

	▭	⌀	▣
0°	100x85 mm	105 mm	95x95 mm
45°	65x60 mm	65 mm	65x65 mm

	WATT	mm	Z/1"	MI/min	a x b x h mm	Kg
782 XL	950	1335x13x0,65	8/12*	60/80	730x390x500	16
783 XL	950	1335x13x0,65	8/12*	30 ÷ 80	730x390x500	16

*Standard bimetal cobalt blade | De serie hoja bimetálica al cobalto · 230 Volt - Hz 50 single-phase motor - Motor monofásico 230 Volt - Hz 50

782 XL

783 XL

BLADES-HOJAS PAG. 36 | ACCESSORIES-ACCESORIOS PAG. 37