



## **SPECIFICATIONS**

**Cutter Capacity:** 35mm Depth of Cut: 50mm Drill Chunk Capacity: 13mm No Load Speed: **850RPM** 1050W Motor Specification: Magnet Adhesion: 80000N Length: 245mm Height: 435mm Width: 155mm 160 x 80mm Magnet Size: 12KG Weight: 110/230V Motor: Stroke: 105mm

## **KEY FEATURES**

- **CUTTER CAPACITY**
- **DEPTH OF CUT** 50mm
- **TWIST DRILL CAPACITY**
- KG

WEIGHT **12KG** 

**MAGNET SIZE** 

160 x 80mm

- **MOTOR** 1050W

- CARRY CASE
  - **ALLEN KEYS**

**INCLUDED** 

- SAFETY STRAP
- **INTERNAL COOLANT SYSTEM**



### **PART CODE:**

Commando 35/1 (110V) Commando 35/3 (230V)

## **SPECIFICATIONS**

Cutter Capacity	40mm
Depth of Cut	50mm
Drill Chuck Capacity	13mm
Countersink	30mm
Tapping	NO
No Load Speed	270 - 610RPM
Motor Specification	1100W
Magnet Adhesion	8000N
Length	265mm
Height	510mm
Width	180mm
Magnet Size	165 x 80mm
Weight	14KG
Motor	110/230V
Stroke	85mm

Cutter Capacity	40mm
Depth of Cut	50mm
Orill Chuck Capacity	13mm
Countersink	30mm
Tapping	NO
No Load Speed	270 - 610RPM
Motor Specification	1100W
Magnet Adhesion	8000N
_ength	265mm
Height	510mm
Width	180mm
Magnet Size	165 x 80mm
Weight	14KG
Motor	110/230V
Stroke	85mm

# **KEY FEATURES**

## **INCLUDED**

A MORE POWERFUL

**ADDED FLEXIBILITY** 

Ideal for countersinking and using twist

drills, this unit is supplied with a chuck as

standard and is a great all round tool for

**MOTOR AND THE** 

OF 6 SPEEDS.

both workshops and sites.

COMMANDO 4.0



**CUTTER CAPACITY** 



**DEPTH OF CUT** 



COUNTERSINK

**TWIST DRILL CAPACITY** 



**WEIGHT** 14 KG

**30mm** 



**MAGNET SIZE** 165 x 80mm



- CARRY CASE
- ALLEN KEYS
- SAFETY STRAP • 13mm DRILL CHUCK
- **INTERNAL COOLANT SYSTEM**



11

PART CODE:

Commando 40/1 (110V) Commando 40/3 (230V)

Rotabroach **POWER To Cut Metal.**