

SPECIFICATIONS

Cutter Capacity 75mm 75mm Depth of Cut Twist Drill Capacity 26mm **Drill Chuck Capacity** 16mm MT3 Morse Taper Countersink 40mm M24 Tapping No Load Speed 70 -500RPM Motor Specification 1800W 18500N Magnet Adhesion Length 375mm Height 713mm Width 214mm 220 x 114mm Magnet Size 23KG Weight Motor 110/230V Stroke 185mm

24

KEY FEATURES

INCLUDED





DEPTH OF CUT



TWIST DRILL CAPACITY
26mm



COUNTERSINK 40mm



TAPPING M24



WEIGHT 23KG



MAGNET SIZE



MOTOR 110/230V

INTERNAL COOLANT SYSTEM

- 16mm CHUCK
- ARBOR ASSEMBLY 6mm HEXAGONAL SPANNER INCLUDED
- SAFETY GLASSES
- ARBOR SHANK
- DRIFT
- SAFETY STRAP
- 3mm HEXAGONAL SPANNER
- STATIONARY RINGS
- PILOT PIN

PART CODE:

Element75/1 (110V) Element75/3 (230V)

SPECIFICATIONS

Cutter Capacity 100mm 100mm Depth of Cut Twist Drill Capacity 32mm **Drill Chuck Capacity** 16mm MT3 Morse Taper Countersink 40mm **M30** Tapping No Load Speed 45 -700RPM Motor Specification 2000W 20000N Magnet Adhesion Length 370mm Height 733mm Width 230mm 228 x 114mm Magnet Size Weight **25KG** Motor 110/230V Stroke 200mm

K

KEY FEATURES

CUTTER CAPACITY



DEPTH OF CUT



TWIST DRILL CAPACITY
32mm



COUNTERSINK 40mm



TAPPING M30

WEIGHT

MAGNET SIZE

228 x 114mm



25KG



MOTOR 110/230V

CUT SMART.

- INTERNAL COOLANT SYSTEM
- 16mm CHUCK

INCLUDED

DESIGNED FOR LARGER

DIAMETER DRILLING.

With 4 gears and 24 forward and reverse speeds, gearing is optimised for drilling

holes to 100mm diameter. The Element™

cut and user safety. Also available with

100 is equipped with CutSmart™ technology to enhance tool life, speed of

swivel base option.

- ARBOR ASSEMBLY 6mm HEXAGONAL SPANNER INCLUDED
- SAFETY GLASSES
- ARBOR SHANK
- DRIFT
- SAFETY STRAP
- 3mm HEXAGONAL SPANNER
- STATIONARY RINGS
- PILOT PIN

PART CODE:

Element100/1 (110V) Element100/3 (230V)

Rotabroach POWER To Cut Metal.