

SPECIFICATIONS

Cutter Capacity 32mm 35mm Depth of Cut **Drill Chuck Capacity** 13mm No Load Speed 600RPM 850W Motor Specification Magnet Adhesion 10000N Length 270mm Height 414mm Width 165mm 180 x 90mm Magnet Size **12KG** Weight 110/230V Motor Stroke 65mm

KEY FEATURES





DEPTH OF CUT



TWIST DRILL CAPACITY



WEIGHT 12KG



MAGNET SIZE 90 x 180mm



MOTOR 110/230V

INCLUDED

- **CARRY CASE**
- **SAFETY STRAP**
- 4mm A/F TEE HANDLED **HEXAGON KEY**
- 6mm HEXAGON KEY
- **INTERNAL COOLANT SYSTEM**
- **DRILL CHUCK ADAPTOR**
- DRILL CHUCK AND KEY
- **SAFETY GLASSES**

PART CODE:

Element30/1 (110V) Element30/3 (230V)

SPECIFICATIONS

Cutter Capacity	40mm
Depth of Cut	50mm
Drill Chuck Capacity	13mm
No Load Speed	300 - 600RPM
Motor Specification	1200W
Magnet Adhesion	10000N
Length	285mm
Height	514mm
Width	185mm
Magnet Size	180 x 90mm
Weight	13KG
Motor	110/230V
Stroke	80mm

Cutter Capacity	40mm
Depth of Cut	50mm
Drill Chuck Capacity	13mm
No Load Speed	300 - 600RPM
Motor Specification	1200W
Magnet Adhesion	10000N
Length	285mm
Height	514mm
Width	185mm
Magnet Size	180 x 90mm
Weight	13KG
Motor	110/230V
Stroke	80mm

KEY FEATURES

INCLUDED

ELEMENT.40

THE ELEMENT™ 40

FUNCTIONALITY.

Capable of countersinking and larger diameter drilling; featuring a two speed

gearbox, the user is able to select the right

with CutSmart™ technology to enhance

tool life, speed of cut and user safety.

CUT SMART.

speed for the drilling diameter. It is also fitted

DELIVERS INCREASED

CUTTER CAPACITY



DEPTH OF CUT



TWIST DRILL CAPACITY



COUNTERSINK 30mm



WEIGHT 13KG



MAGNET SIZE 180 x 90mm



110/230V

- **INTERNAL COOLANT SYSTEM**
- SAFETY STRAP

CARRY CASE

- 4mm A/F TEE HANDLED **HEXAGON KEY**
- 3mm HEXAGON KEY
- 6mm HEXAGON KEY
- DRILL CHUCK ADAPTOR
- **DRILL CHUCK AND KEY**
- SAFETY GLASSES

PART CODE:

Element40/1 (110V) Element40/3 (230V)

17

Rotabroach **POWER To Cut Metal.**