

22



SPECIFICATIONS

Cu De Со No Mo Ma Ler He Wi Ma We Mo Str

utter Capacity	50mm	
epth of Cut	50mm	CUTTE
ountersink	30mm*	50mm
o Load Speed	250-500RPM	DEPTH 50mm
lotor Specification	1200W	— HEIGH
lagnet Adhesion	10000N	H 179mm
ength	334mm	TWIST
eight	179mm	N/A
/idth	100mm	
lagnet Size	192 x 82mm	30mm ³
/eight	11KG	WEIGH
lotor	110/230V	11K G
troke	62mm	* MAGNI
		100 0



KEY FEATURES

ter Capacity	50mm		
th of Cut	50mm	Î	CUTTER CAPAC
ıntersink	30mm*	_	50mm
_oad Speed	250-500RPM	٦////	DEPTH OF CUT 50mm
or Specification	1200W		
gnet Adhesion	10000N	Ŭ H	HEIGHT 179mm
gth	334mm		TWIST DRILL CA
ght	179mm		N/A
th	100mm		COUNTERSINK
gnet Size	192 x 82mm		30mm*
ght	11KG		WEIGHT
or	110/230V	KG	11KG
		4	



APACITY



110/230V

INCLUDED

- CARRY CASE
- FIXED GUARD
- SAFETY STRAP
- COOLANT BOTTLE
- 4mm HEXAGONAL WRENCH
- COOLANT BOTTLE
- RATCHET HANDLE
- SAFETY STRAP
- SAFETY GOGGLES

PART CODE:

Element50/1 Low Profile (110V) Element50/3 Low Profile (230V)

23

Rotabroach POWER To Cut Metal.

^{*}Requires an extension arbor RD32059.