

## **SPECIFICATIONS**

### **Cutter Capacity** 40mm Depth of Cut 50mm **Drill Chuck Capacity** 13mm No Load Speed 300-600RPM Motor Specification 1200W Magnet Adhesion **5000N** 285mm Length Height 514mm Width 185mm 210 x 90mm Magnet Size 13KG Weight 110/230V Motor 85mm Stroke

## **KEY FEATURES**

## INCLUDED





**CUTTER CAPACITY** 



**DEPTH OF CUT** 



**TWIST DRILL CAPACITY 13mm** 



COUNTERSINK 30<sub>mm</sub>



WEIGHT 13KG



**MAGNET SIZE** 180 x 90mm



110/230V

- **CARRY CASE**
- **INTERNAL COOLANT SYSTEM**
- SAFETY STRAP
- 4mm A/F TEE HANDLED **HEXAGON KEY**
- **3mm HEXAGON KEY**
- 6mm HEXAGON KEY
- DRILL CHUCK ADAPTOR
- **DRILL CHUCK AND KEY**
- SAFETY GLASSES

### **PART CODE:**

Element40/1 Permanent Magnet (110V) Element40/3 Permanent Magnet (230V)

# **SPECIFICATIONS**

# Cutte Dept Twist Drill Mors Cour Tapp No L Moto Mag Leng Heig Widt Mag Weig Moto Strol

er Capacity	50mm
th of Cut	50mm
st Drill Capacity	20mm
Chuck Capacity	13mm
se Taper	MT2
ntersink	30mm
oing	M20
oad Speed	100 - 500RPM
or Specification	1500W
net Adhesion	13500N
gth	315mm
jht	586mm
th	195mm
net Size	200 x 98mm
ght	15KG
or	110/230V
ke	140mm

# **KEY FEATURES**

ELEMENT.50





**DEPTH OF CUT** 



**TWIST DRILL CAPACITY** 



**COUNTERSINK 30mm** 



**TAPPING M20** 

WEIGHT





200 x 98mm



110/230V

INCLUDED

- CARRY CASE
- INTERNAL COOLANT SYSTEM

**A LARGE** 

MACHINE.

**CAPACITY, MT2** 

Fitted with two gears and 12 forward and reverse speeds, the Element™ 50 is perfect for drilling, countersinking and

threading. Weighing just 15kg this is a

tool life, speed of cut and user safety.

CUT SMART.

versatile tool for workshop and site use, with CutSmart™ technology to enhance

- SAFETY STRAP
- STATIONARY RING
- 3mm HEXAGON KEY
- 6mm HEXAGON KEY
- ARBOR ASSEMBLY
- 13mm CHUCK
- DRILL CHUCK ADAPTOR
- DRILL CHUCK AND KEY
- SAFETY GLASSES

### **PART CODE:**

Element50/1 (110V) Element50/3 (230V)

19

Rotabroach **POWER To Cut Metal.**