

### **SPECIFICATIONS**

#### **Cutter Capacity** 36mm **320RPM** No Load Speed 1500W 2.0HP Motor Specification Magnet Adhesion N/A Length 540mm 420mm Height Width 420mm Weight **20KG** 4 STROKE Motor **PETROL**

34

#### **KEY FEATURES**



### **INCLUDED**

- 4mm A/F TEE HANDLED **HEXAGON KEY**
- **COOLANT FEED DISPENSER**
- 8mm HEX KEY
- 3/16 LONG HEX KEY

#### **APPROVALS**







**PART CODE:** 

**RD074** 

# **SPECIFICATIONS**

Cutter Capacity	40mm
Twist Drill Capacity	13.5mm
No Load Speed	270-610RPM
Motor Specification	1100W
Length	640mm
Height	320mm
Width	180mm
Weight	16KG
Motor	110/230V

Cutter Capacity	40mm
Twist Drill Capacity	13.5mm
No Load Speed	270-610RPM
Motor Specification	1100W
Length	640mm
Height	320mm
Width	180mm
Weight	16KG
Motor	110/230V

KEY	FEAT	<b>TURES</b>

**CUTTER CAPACITY** 

## **INCLUDED**

RHINOE

THE RHINO E IS AN

FOR RAIL DRILLING

**APPLICATIONS.** 

Ideal for tunnel work and confined spaces with poor ventilation,

this rail drill is equipped with a

mechanical clutch and thermal

machine durability.

overload protection for increased

**ELECTRIC RAIL MACHINE,** 

**SPECIFICALLY DESIGNED** 

- 4mm A/F TEE HANDLED **HEXAGON KEY**
- **3mm HEXAGON KEY**
- COOLANT FEED DISPENSER

CM/127/1A (110V) CM/127/3A (230V)

35

MOTOR 110/230V

16KG

KG

Rotabroach **POWER To Cut Metal.**